

WOODS® BATWING® SINGLE-WING ROTARY CUTTER

Model Overview



Over 50 years ago, Woods® introduced the original flexwing rotary cutter, the Batwing®. It instantly became a household name for flexwing cutters. Why? Because you needed a rugged piece of equipment that could tackle the toughest rural mowing jobs ... and the Batwing delivered.

This meticulously engineered attachment has a cutting capacity ranging from 6,4 cm to 11,4 cm in diameter taming unruly waterways, pastures, and fields.

SPECIFICATIONS	BW10.50	BW10.60	BW10.70	BW13.70
PTO Horsepower	45 - 200	55 - 275	64 - 300	70 - 300
Side Frame Depth	33 cm		31,8 cm	
Cutting Width	3,20 m		4,10 m	
Cutting Height	5 - 38 cm			
Cutting Capacity Diameter	6,4 cm	10 cm	11,4 cm	10 cm
Transport Width	2,44 m		2,54 m	
Center & Wing Deck Thickness	3,43 mm	4,54 mm	6,4 mm	3,43 mm
Side Frame Thickness	6,4 mm			
Weight / Tongue Weight	1833 kg / 522 kg	1996 kg / 612 kg	2400 kg / 676 kg	3855 kg / 1225 kg
Main / Wing Driveline Rating	CAT 6 CV / CAT 4		CAT 6 CV / CAT 5	
Output Shaft Diameter	5 cm	7,6 cm		6 cm
Splitter / Wings Gearbox Rating	210 / 200 hp	275 / 225 hp		250 / 120 hp
Blade Tip Speed	76,2 mps at 540 rpm 81,3 mps at 1000 rpm	79,75 mps at 540 rpm 81,3 mps at 1000 rpm		78,48 mps at 540 rpm 84,58 mps at 1000 rpm
Wing Flex	90° up, 22° down			
Gearbox Warranty	6 year			
Options	<ul style="list-style-type: none"> ▪ double row chain shielding ▪ dual wheels ▪ LED lights 	<ul style="list-style-type: none"> ▪ double row chain shielding ▪ dual wheels ▪ LED lights ▪ shredding kit ▪ deck ring ▪ spring axle ▪ walking tandem 		<ul style="list-style-type: none"> ▪ double row chain shielding ▪ dual wheels ▪ spring axle ▪ walking tandem



SUPERIOR DESIGN ▪ **SUPERIOR DURABILITY** ▪ **SUPERIOR STYLE**